



SOKYMAT

**TEAR SHAPE
Mifare® 1K**

Description	Proximity Keyfob designed to suit most 13.56 MHz applications		
IC type:	Mifare® 1K MF1 IC S50		
Physical:	Thickness:	4.8 mm	± 0.30 mm
	Length:	40 mm	± 0.30 mm
	Width:	31 mm	± 0.30 mm
	Color:	Black (upon request: blue, red)	
Electrical:	Operating Frequency:	13.56 MHz	
Storage temp:	-25°C to +80 °C	(-13°F to +176 °F)	ISO/IEC 10373
Operating temp:	-25°C to +50 °C	(-13°F to +122 °F)	ISO/IEC 10373
Mechanical:	Drop test 10 times 10 cycles (1.8m)		
Resistance:	The Keyfob is designed to resist common stress known from access control and time and attendance systems		
Material:	Polycarbonate		
Immersion:	Water IP67	ISO/IEC 60529	
Printing:	One side printable with various technologies		
Options:	For full options list, please visit our website: www.aaitg.com		
Part number:	607031-0XX		

© HID reserves the right to change any information or data in this document without prior notice. The distribution and the update of this document is not controlled. HID declines all responsibility for the use of products with any other specifications but the ones mentioned above. Any additional requirement for a specific customer application has to be validated by the customer himself at his own responsibility. Where application information is given, it is only advisory and does not form part of the specification.
CLF 3.3.2.36 - V1 - DefKey: 310414 - 29.10.2008 - Page: 1 of 1