



sokymot

**ISO Card
Q5**

Description	Proximity ISO card, flexible card designed to suit most 125 kHz proximity systems		
IC type:	Q5 (5555)		
Physical:	Thickness:	0.76 mm	± 0.08 mm
	Length:	85.60 mm	± 0.12 mm
	Width:	53.98 mm	± 0.05 mm
	Color:	White / white	
Electrical:	Operating Frequency:	125 kHz	± 6 kHz
Operating temp:	-35°C to +50 °C	(-30 °F to +122 °F)	ISO/IEC 10373
Resistance:	Dynamic bending and torsion stress tested		ISO/IEC 7816-1 and 10373
Material:	PVC, white / white (glossy)		
Slots:	Different positions for slots are available		
Contact module:	Customer may embed a contact module at ISO position		ISO/IEC 7816-1
Magnetic stripe:	HiCo and LoCo magstripe in ISO position upon request		
Printing:	Both sides are fully printable with various technologies		
Options:	For full options list, please visit our website: www.aaitg.com		
Part number:	61240X		

© ASSA ABLOY ITG reserves the right to change any information or data in this document without prior notice. The distribution and the update of this document is not controlled. ASSA ABLOY ITG declines all responsibility for the use of products with any other specifications but the ones mentioned above. Any additional requirement for a specific customer application has to be validated by the customer himself at his own responsibility. Where application information is given, it is only advisory and does not form part of the specification.

CLF 3.3.2.10 – V4 - DefKey: 3314099 - 11.09.2007 - Page: 1 of 1

ASSA ABLOY Identification Technologies GmbH, Am Klängenweg 6A, 65396 Walluf, Germany Tel: +49 6123 791 0 Fax: -110 email: info@aaitg.com web: www.aaitg.com